


IQ8MC Microinverter

Our newest IQ8 Series Microinverters^{1,2} are the industry's first microgrid-forming³, software-defined microinverters with split-phase power conversion capability to convert DC power to AC power efficiently.



Key specifications	IQ8MC-72-M-US/ IQ8MC-72-M-DOM-US @240 VAC	IQ8MC-72-M-US/ IQ8MC-72-M-DOM-US @208 VAC
Peak output power	330 VA	315 VA
Nominal grid voltage (L-L)	240 V split-phase (L-L), 180°	208 V single-phase (L-L), 120°
Nominal frequency	60 Hz	
CEC weighted efficiency	97%	96.5%
Maximum input DC voltage	60 V	
MPPT voltage range	25–45 V	
Maximum module I_{SC}	20 A	
Ambient temperature range	–40°F to 149°F (–40°C to 65°C)	



Simple

- Lightweight and compact with plug-and-play connectors
- Power line communication (PLC) between components
- Faster installation with simple two-wire cabling

Reliable

- Produces power even when the grid is down³
- More than one million cumulative hours of testing
- Industry-leading limited warranty of up to 25 years
- Class II double-insulated enclosure
- Optimized for the latest high-powered PV modules

Microgrid-forming

- Complies with the latest advanced grid support
- Remote automatic updates for the latest grid requirements
- Configurable to support a wide range of grid profiles
- Meets CA Rule 21 (UL 1741-SA) and IEEE 1547:2018 (UL 1741-SB 3rd Ed.)

¹For details, see the "Compatibility with IQ7 Series Microinverters" section.

²IQ Microinverters ship with default settings that meet North America's IEEE 1547 interconnection standard requirements. Region-specific adjustments may be requested by an Authority Having Jurisdiction (AHJ) or utility representative, according to the IEEE 1547 interconnection standard. Use an IQ Gateway to make these changes during installation.

³Meets UL 1741 only when installed with IQ System Controller 2 or 3.

Input data (DC)	Units	IQ8MC-72-M-US/IQ8MC-72-M-DOM-US	
Commonly used module pairings ⁴	W	260–460	
Module compatibility	—	To meet compatibility, PV modules must be within the following max. input DC voltage and max. module I_{sc} . Module compatibility can be checked at https://enphase.com/installers/microinverters/calculator .	
MPPT voltage range	V	25–45	
Operating range	V	18–58	
Min./Max. start voltage	V	22/58	
Max. input DC voltage	V	60	
Max. continuous operating DC current	A	14	
Max. input DC short-circuit current	A	25	
Max. module I_{sc}	A	20	
Overvoltage class DC port	—	II	
DC port backfeed current	mA	0	
PV array configuration	—	Ungrounded array; no additional DC side protection required; AC side protection requires a maximum of 20 A per branch circuit.	
Output data (AC)	Units	IQ8MC-72-M-US/IQ8MC-72-M-DOM-US @240 VAC	IQ8MC-72-M-US/IQ8MC-72-M-DOM-US @208 VAC
Peak output power	VA	330	315
Max. continuous output power	VA	320	310
Nominal grid voltage (L-L)	V	240, split-phase (L-L), 180°	208, single-phase (L-L), 120°
Min./Max. grid voltage ⁵	V	211–264	183–229
Max. continuous output current	A	1.33	1.49
Nominal frequency	Hz	60	
Extended frequency range	Hz	47–68	
AC short-circuit fault current over three cycles	A_{rms}	2.70	
Max. units per 20 A (L-L) branch circuit ⁶	—	12	10
Total harmonic distortion	%	<5	
Overvoltage class AC port	—	III	
AC port backfeed current	mA	18	
Power factor setting	—	1.0	
Grid-tied power factor (adjustable)	—	0.85 leading ... 0.85 lagging	
Peak efficiency	%	97.4	97.2
CEC weighted efficiency	%	97.0	96.5
Nighttime power consumption	mW	33	25
Mechanical data	IQ8MC-72-M-US/IQ8MC-72-M-DOM-US		
Ambient temperature range	–40°F to 149°F (–40°C to 65°C)		

⁴ No enforced DC/AC ratio.

⁵ Nominal voltage range can be extended beyond nominal if required by the utility.

⁶ Limits may vary. Refer to local requirements to define the number of microinverters per branch in your area.

Mechanical data	IQ8MC-72-M-US/IQ8MC-72-M-DOM-US
Relative humidity range	4–100% (condensing)
DC connector type	Stäubli MC4
Dimensions (W × H × D); Weight	6.9" × 8.3" × 1.2" (175 mm × 212 mm × 30.2 mm); 2.43 lb (1.1 kg)
Cooling	Natural convection—no fans
Approved for wet locations; Pollution degree	Yes; PD3
Enclosure	Class II double-insulated, corrosion-resistant polymeric enclosure
Environmental category; UV exposure rating	NEMA Type 6; outdoor

Compliance	IQ8MC-72-M-US/IQ8MC-72-M-DOM-US
Certifications	CA Rule 21 (UL 1741-SA), UL 62109-1, UL 62109-2, IEEE 1547:2018 (UL 1741-SB 3rd Ed.), FCC Part 15 Class B, ICES-0003 Class B, CAN/CSA-C22.2 No. 107.1-01, 330, CAN/CSA-C22.3 No. 9. This product is UL Listed as PV rapid shutdown equipment and conforms with NEC 2014, NEC 2017, NEC 2020, NEC 2023 section 690.12, and C22.1-2018 Rule 64-218 rapid shutdown of PV systems for AC and DC conductors when installed according to the manufacturer's instructions.

Compatibility with IQ7 Series Microinverters

- IQ8 Series Microinverters can be added to existing IQ7 systems on the same IQ Gateway/IQ Combiner/IQ System Controller only in the following configurations: (i) Solar Only or (ii) Solar Plus Battery (IQ Battery 3/10 or IQ Battery 5P) grid-tied or with backup with IQ System Controller 3/3G/3M and IQ Meter Collar.
- IQ7 Series Microinverters cannot be added to a site with existing IQ8 Series Microinverters on the same gateway.
- A mixed system with both IQ7 and IQ8 Series Microinverters does not support IQ8-specific features such as PCS or the Sunlight Jump Start feature.
- The rated continuous power output of the IQ7 and IQ8 Microinverter arrays must not exceed 150% of the IQ Battery's rated power output. If this ratio is exceeded, PV shedding must be implemented to reduce excess PV generation during transitions to off-grid mode.

Components of the Enphase Energy System



IQ Battery

All-in-one AC-coupled storage solution that integrates seamlessly with your solar energy system, providing reliable backup power and intelligent energy management for maximum performance and energy savings.




IQ System Controller

The IQ System Controller connects the home to the grid power, IQ Batteries, generator, and solar PV with microinverters.



IQ Combiner/IQ Gateway

The IQ Combiner/IQ Gateway is a device that performs energy management, provides internet connectivity, and integrates with the IQ Series Microinverters to provide complete control and insights into the Enphase Energy System.



IQ Cable

The IQ Cable is a continuous-length 12 AWG cable with pre-installed connectors for IQ Microinverters that support faster, simpler, and more reliable installations. The cable is handled like standard outdoor-rated electrical wire, allowing it to be cut, spliced, and extended as needed.

Revision history

Revision	Date	Description
DSH-00049-7.0	July 2026	Updated the compliance information.
DSH-00049-6.0	October 2025	Updated information on backward compatibility with IQ8/IQ7 Series Microinverters.
DSH-00049-5.0	December 2024	Updated information on backward compatibility with IQ7 Series Microinverters.
DSH-00049-4.0	February 2024	Added information about IEEE 1547 interconnection standard requirements.
DSH-00049-3.0	October 2023	Included NEC 2023 specification in the “Compliance” section.
DSH-00049-2.0	September 2023	Updated module compatibility information.
DSH-00049-1.0	May 2023	Preliminary release.